



VTK Series

65"

75"

86"

Smart Interactive Display

SOLUSI IDEAL UNTUK KUALITAS GAMBAR YANG TAJAM DAN JERNIH

VTK Series mendukung solusi hybrid learning dan hybrid working dengan sistem kolaboratif, konektivitas luas, kemudahan penggunaan, teknologi tulisan, dan pembelajaran dinamis yang dapat berkolaborasi dengan siapa pun dan di mana pun.



UHD Resolution with 400 nits



Zero Bonding Technology



Built-in Voice Tracking Camera and Microphone



DUAL OS



Full function Type-C port available



OCR functions for Smart Handwriting Recognition



4K UI for All the System Page



4K@50fps Screen Recording



Screen Splitting Available

SPECIFICATIONS

VTK Series

VN-VTK Smart Display series



Display			
Model	VN-IF65-VTK / VN-IF75-VTK / VN-IF86-VTK		
Screen Size	65 inch	75 inch	86 inch
Display Size	1428.48 × 803.52	1649.74 × 927.94	1895.04 × 1065.96
Native Resolution	3840(H) × 2160(V)		
Aspect Ratio	16 : 9		
Brightness	400 cd/m ²		
Contrast	1200 : 1		
View Angle	178°(H) / 178°(V)		
Display Color	1.07 billion colors		
Response Time	8ms		

Internal Player	
O/S	Android 12.0
CPU	8*A55 ARM Cortex
GPU	Mali-G52*4
RAM/ROM	6GB DDR4 / 64GB EMMC
Input	HDMI IN *2 ,HDMI Out*1 , DP*1, Type-C*1(15W), USB3.0*3(2 Public), MIC IN*1 USB 2.0*1, USB Touch*1, Micro-SD*1, RJ45*2, RS232*1
Output	HDMI OUT*1, Type C*1, SPDIF out Earphone*1
Front Connection	HMDI IN*1, USB 3.0 *3, TOUCH USB*1, TYPE C*1(PD65w)
Wi-Fi	Wi-Fi 6, Wi-Fi 802.11/a/b/g /n/ac (2.4G+5G) ; Hotspot 5Ghz
Built-In Camera / Microphone	(13MP + 8 MIC + 120 Degree)
OPS	OPS i5 / 8 + 256GB (Optional)

IR Touch	
Touch Points	40 touch points
Response Time	<8ms
Touch Accuracy	1mm
Pen and Touch Differentiation	Yes
Pen Included	2 stylus
Compatibility	Windows / Linux / Android / Chrome

Sound / Speaker	
Speaker Type	2pcs Built in,Left/Right
Speaker Output	20W x 2
Audio Stereo	Balance, automatic volume control, surround sound, equalizer

Power			
Power Consumption	≤ 230W	≤ 300W	≤ 400W
Power Supply	AC100-240V~ 50/60Hz		
Stand By	< 0.5W		

Environment Condition	
Operation Temperature	0°C- 40°C
Operation Humidity	10% - 80%RH
Storage Temperature	-10°C ~ 45°C
Storage Humidity	5% - 90%RH

Physical			
Model	VN-IF65-VTK	VN-IF75-VTK	VN-IF86-VTK
Unit Dimension (LxHxW)mm	1486 x 909 x 90	1707 x 1034 x 90.6	1953 x 1173 x 90.6
Package Dimension (LxHxW)mm	1665 x 1045 x 230	1880 x 1160 x 230	2161 x1337 x230
Net Weight (Kg)	40	55	67
Gross Weight	54	76	98
VESA Mount	500 x 400mm	600 x 400mm	800 x 400mm
Standing Mobile Bracket (Optional) Packing Dimension	106.5 x 81 x 20cm		
Standing Mobile Bracket (Optional) Packing Gross Weight	38kg		